

Applic. No. 10/667,717

Amdt. dated August 3, 2006

Reply to Office action of April 3, 2006

RECEIVED  
CENTRAL FAX CENTER  
AUG 13 2006

Claim Amendments

This listing of the claims will replace all prior versions,  
and listings, of claims in the application:

Claim 1 (currently amended): An optical sensing head for  
sensing laser radiation reflected by an optical data memory  
and for reading out the optical data memory, the optical  
sensing head comprising:

a substrate having a main surface extending along a first main  
plane;

an edge-emitting laser component for emitting laser radiation  
along an irradiation axis oriented essentially parallel to  
said first main plane, said laser component configured on said  
main surface of said substrate;

a deflection device configured on said main surface of said  
substrate, said deflection device for providing deflected  
laser radiation in a direction essentially perpendicular to  
said main surface by deflecting the laser radiation emitted by  
said laser component;

Applic. No. 10/667,717

Amdt. dated August 3, 2006

Reply to Office action of April 3, 2006

at least one signal detector for sensing the laser radiation reflected by the optical data memory;

an optical element for guiding the deflected laser radiation to the optical data memory and for guiding the laser radiation reflected by the optical data memory to said signal detector; and

a supporting element connecting said optical element to said substrate;

at least one of said supporting element and said deflection device being produced from glass and being nondetachably connected to said substrate by an anodic bond.

Claim 2 (original): The optical sensing head according to claim 1, wherein said deflection device also serves as a supporting element for connecting said optical element to said substrate.

Claim 3 (original): The optical sensing head according to claim 1, wherein:

said signal detector is an irradiation-direction signal detector configured on said main surface of said substrate;

Applic. No. 10/667,717

Amdt. dated August 3, 2006

Reply to Office action of April 3, 2006

said irradiation-direction signal detector is configured on  
said irradiation axis of said laser component; and

said irradiation-direction signal detector is configured  
downstream of said deflection device with respect to a  
direction of irradiation of the laser radiation emitted by  
said laser component.

Claim 4 (original): The optical sensing head according to  
claim 1, further comprising:

an opposite-direction signal detector configured on said main  
surface of said substrate;

said opposite-direction signal detector configured on said  
irradiation axis of said laser component; and

with respect to said laser component, said opposite-direction  
signal detector configured in a direction opposite to a  
direction of the laser radiation emitted by said laser  
component.

Claim 5 (previously presented): The optical sensing head  
according to claim 4, wherein said supporting element is

Applic. No. 10/667,717  
Amdt. dated August 3, 2006  
Reply to Office action of April 3, 2006

configured between said laser component and said opposite-direction signal detector.

Claim 6 (original): The optical sensing head according to claim 5, wherein:

said supporting element, which is configured between said laser component and said opposite-direction signal detector, has a surface facing said laser component; and

said surface of said supporting element has a metallic or dielectric mirrored layer.

Claim 7 (original): The optical sensing head according to claim 5, wherein:

said supporting element, which is configured between said laser component and said opposite-direction signal detector, has a surface facing said laser component; and

said surface of said supporting element has an absorption layer.

Claim 8 (original): The optical sensing head according to claim 5, wherein said supporting element, which is configured

Applic. No. 10/667,717

Amdt. dated August 3, 2006

Reply to Office action of April 3, 2006

between said laser component and said opposite-direction signal detector, is embodied as a deflection device for deflecting stray light of said laser component away from said opposite-direction signal detector.

Claim 9 (original): The optical sensing head according to claim 5, wherein said supporting element, which is configured between said laser component and said opposite-direction signal detector, is embodied as a deflection device for deflecting stray light of said laser component away from said opposite-direction signal detector in a direction essentially perpendicular to said main surface.

Claim 10 (original): The optical sensing head according to claim 1, wherein said signal detector is formed in said substrate.

Claim 11 (original): The optical sensing head according to claim 10, wherein said signal detector includes an array of PIN photodiodes formed in said substrate.

Claim 12 (original): The optical sensing head according to claim 1, further comprising:

Applic. No. 10/667,717

Amdt. dated August 3, 2006

Reply to Office action of April 3, 2006

a monitor detector for checking an irradiation power of said  
laser component;

said monitor detector integrated on said substrate.

Claim 13 (original): The optical sensing head according to  
claim 1, further comprising:

a plurality of detectors, said plurality of detectors  
including said at least one signal detector;

a plurality of supporting elements;

said deflection device embodied as a deflection mirror;

said plurality of supporting elements configured beside said  
deflection mirror;

said plurality of detectors configured between said deflection  
mirror and said plurality of supporting elements;

said optical element mounted on said plurality of supporting  
elements.

Applic. No. 10/667,717

Amdt. dated August 3, 2006

Reply to Office action of April 3, 2006

Claim 14 (original): The optical sensing head according to claim 1, wherein said substrate is formed by a silicon substrate.

Claim 15 (cancelled).

Claim 16 (original): The optical sensing head according to claim 1, wherein said main surface of said substrate has an area of 10 mm<sup>2</sup> or less.

Claim 17 (cancelled).

Claim 18 (currently amended): A method for fabricating an optical sensing head, which comprises:

providing the optical sensing head according to claim 1; and

fabricating the deflection device by:

sawing a glass wafer into individual strips,

obtaining ground surfaces by grinding surfaces onto the strips at a predetermined angle,

Applic. No. 10/667,717

Amdt. dated August 3, 2006

Reply to Office action of April 3, 2006

coating the ground surfaces with a highly reflective mirrored layer to obtain deflection prisms for deflecting laser beams, and

nondetachably orientating and connecting the deflection prisms to the substrate, and carrying out the connecting by anodic bonding.

Claim 19 (cancelled).

Claim 20 (original): The method according to claim 18, which further comprises:

before performing the step of sawing the glass wafer, metalizing regions on a front side of the glass wafer;

the regions providing soldering surfaces for connecting optical components to the substrate after performing the step of connecting the deflection prisms to the substrate.

Claim 21 (original): The method according to claim 18, which further comprises:

Applic. No. 10/667,717

Amdt. dated August 3, 2006

Reply to Office action of April 3, 2006

before performing the step of sawing the glass wafer,  
introducing trenches into a rear side of the glass wafer by  
sandblasting.

Claim 22 (original): The method according to claim 18, which  
further comprises:

when performing the step of fabricating the deflection device,  
concurrently fabricating supporting elements from the glass  
wafer.

Claim 23 (original): The method according to claim 18, which  
further comprises:

forming an array of PIN photodiodes in the substrate;

the PIN photodiodes serving as a signal detector or as a  
plurality of signal detectors.

Claim 24 (original): The method according to claim 18,  
wherein the predetermined angle is approximately 45°.